



LAMIERE GRECATE - SERIE LGH

Scheda tecnica

Articoli:

LGH 075 Z10 (Finitura Zincata)

LGH 075 V10 (Finitura Bianco/Grigio)

S		larghezza efficace appoggio : 100 mm																			
mm	$l = m$	1,50	1,75	2,00	2,25	2,50	2,75	3,00	3,25	3,50	3,75	4,00	4,25	4,50	4,75	5,00	5,25	5,50	5,75	6,00	
0,5	$p = daN / m^2$	755	555	420	330	265	220	185	150	115	95	75	60	50							
0,6		925	675	515	405	330	270	225	180	140	110	90	75	60	50						
0,7		1095	805	615	485	390	320	265	205	160	130	105	85	70	60	50					
0,8		1270	930	710	560	450	370	300	235	185	145	120	95	80	65	55					
1		1620	1190	910	715	575	475	365	285	225	180	145	120	100	80	65	55				
1,2		2010	1475	1125	890	715	565	430	335	265	210	170	140	115	95	80	65	55			
1,5		2620	1925	1470	1160	915	680	520	405	320	255	205	170	140	115	95	80	65	55		

S		larghezza efficace appoggio : 100 mm																			
mm	$l = m$	1,50	1,75	2,00	2,25	2,50	2,75	3,00	3,25	3,50	3,75	4,00	4,25	4,50	4,75	5,00	5,25	5,50	5,75	6,00	
0,5	$p = daN / m^2$	350	275	220	180	150	125	105	90	80	70	60	55								
0,6		475	370	295	245	205	170	145	125	110	95	85	75	65	60	50					
0,7		615	480	385	320	265	225	190	165	140	125	110	95	85	80	70	60	55	50		
0,8		740	585	475	395	330	280	240	205	180	155	140	120	110	100	90	80	70	65	55	
1		1005	790	655	535	445	380	325	280	245	215	190	170	150	135	120	110	95	90	80	
1,2		1265	990	875	715	595	505	435	375	325	290	255	225	205	180	160	145	130	120	110	
1,5		1635	1275	1380	1135	950	810	695	605	530	470	415	370	335	300	260	220	190	165	140	

S		larghezza efficace appoggio : 100 mm																			
mm	$l = m$	1,50	1,75	2,00	2,25	2,50	2,75	3,00	3,25	3,50	3,75	4,00	4,25	4,50	4,75	5,00	5,25	5,50	5,75	6,00	
0,5	$p = daN / m^2$	425	330	265	220	185	165	130	115	100	85	75	65	60	55	50					
0,6		575	450	360	300	250	210	180	155	135	120	105	95	85	75	65	60	55	50		
0,7		740	580	465	390	325	275	235	200	175	155	135	120	110	100	90	80	70	65	55	
0,8		890	705	570	480	405	340	295	255	220	195	170	155	135	125	110	95	85	70	60	
1		1210	955	790	650	545	460	395	345	300	265	235	210	190	165	140	120	100	85	75	
1,2		1525	1200	1055	870	725	615	530	460	405	355	315	280	235	195	165	140	120	105	90	
1,5		1975	1545	1660	1375	1155	985	850	740	625	505	410	340	280	235	200	170	145	125	105	

In rosso i carichi limitati da freccia 1/200 l

Nelle tabelle non vengono riportati carichi < 50 daN /m2

Calcoli elaborati con software STA.DATA - Torino - in accordo con norma EN 1993-1-3 con materiale S250GD - EN 10147

SEZIONE LORDA			
J_y	$W_{y,inf}$	$W_{y,sup}$	$W_{y,p}$
cm^4/m	cm^3/m	cm^3/m	cm^3/m
67,00	14,30	24,50	20,07
80,48	16,97	29,18	24,89
92,67	19,98	33,67	28,67
104,98	22,14	38,06	32,79
128,34	27,07	46,52	40,48
150,58	31,76	54,58	47,98
181,87	38,37	65,90	58,86



Codice Prodotto:
LGH 075 Z10 - LGH 075 V10